

TJ HD EQUIPMENT TILT 6" CHANNEL

STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

Deck Width: 82" (81.5" Between Fenders)	Deck Height: 23"	Axles: Tandem Torsion (2 x 8,000 lb.)	Choose the optional Blackwood Pro decking for added durability and grip when wet.
Length: 20' - 24'	Couplers: Bumper Pull, Gooseneck, & Pintle	Load Capacity: 12,750 - 11,520 lbs.	
GVWR: 16,000 lbs.	Weight: 3,520 - 4,480 lbs.	Tilt Angle: 12°	



Our Gravity Tilt uses a hydraulic cylinder and proportioning valve to control the rate of tilt movement for additional safety when loading and unloading.

HYDRAULIC CUSHIONED GRAVITY TILT



Simplify brake maintenance with our Forward Self-Adjusting Brakes, engineered to self-adjust for optimal braking performance. This innovative system reduces downtime and ensures consistent stopping power.

FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard Rubrail, stake pockets and pipe spools. In addition to the built-in stake pockets, the Rubrail provides extra attachment points for securing your load. Customize your trailer further by adding optional D-rings.

CARGO CONTROL STANDARD



Our 30" Diamond plate knife edge tail makes it super-easy to load low clearance equipment like scissor lifts and fork lifts.

KNIFE EDGE TAIL

PJ TRAILERS

Visit pjtrailers.com for a complete list of trailer options.