STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

T1 SINGLE AXLE HD TILT

W Deck Width: 81"	Deck Height: 21"	Axle: 7,000 lb. Drop Axle	Choose the optional Blackwood Pro decking for added durability and grip when wet.
Length: 13', 16'	Couplers: Bumper Pull & Pintle	☆! Load Capacity: 4,800 - 5,140 lbs.	
♥ GVWR: 7,000 lbs.	Weight: 1,860 - 2,200 lbs.	Tilt Angle: 11°	





Our Gravity Tilt uses a hydraulic cylidner and porportioning valve to control the rate of tilt bed movement for additional safety when loading and unloading.

HYDRAULIC CUSHIONED GRAVITY TILT



Simplify brake maintenance with our Forward Self-Adjusting Brakes, engineered to self-adjust for optimal braking performance. This innovative system reduces downtime and ensures consistent stopping power.

FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard stake pockets. Customize your trailer further by adding optional D-rings. (Standard flush-mounted D-ring shown)

CARGO CONTROL STANDARD



Our 26" Diamond plate knife edge taile makes it super-easy to load low clearance equipment like scissor lifts and fork lifts.

KNIFE EDGE TAIL

